

STAINLESS LCD


15"

Specifications




Model Name	STR150L100
Viewable Size Image	15"
Active Display Area(mm)	304.1(H) x 228.1(V)
Pixel Pitch(mm)	0.297(H) x 0.297(V)
Number of Pixels	1024 x 768
Contrast Ratio	700:1 (typ.)
Display Color	16.2M/262K
Brightness(cd/m ²)	400 (typ.)
Viewing Angle(CR>=10)	-80~80(H); -70~70(V)
Synchronization Range	
Horizontal/Vertical	31.5~60.0KHz/60~75Hz
Recommended Resolution	1024x768@60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	12V DC in, with External AC to DC Adapter (100~240V AC)
Power Consumption	20W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive

Remarks: STR150L100 series= VGA input only
STR150L110 series= VGA+Video Input



Mechanical Drawing



Unit:mm

* Note: this is a simplified drawing and some components are not marked in detail. Please contact our sales representative if you need further product information.